

Maxi-Paw™ / Maxi-Paw SAM Performance						
Pressure psi	Nozzle	Radius ft.	Flow gpm	Precip In/h	Precip In/h	
25	06	-	-	-	-	
	07 LA	22	1.5	0.60	0.69	
	07	32	2.2	0.41	0.48	
	08	35	2.8	0.44	0.51	
	10 LA	25	3.4	1.05	1.21	
	10	38	4.2	0.56	0.65	
	12	39	5.5	0.70	0.80	
35	06	37	2.0	0.28	0.32	
	07 LA	23	1.9	0.69	0.80	
	07	37	2.7	0.38	0.44	
	08	38	3.3	0.44	0.51	
	10 LA	29	4.0	0.92	1.06	
	10	41	4.8	0.55	0.64	
	12	42	6.3	0.69	0.79	
45	06	38	2.3	0.31	0.35	
	07 LA	25	2.1	0.65	0.75	
	07	39	3.0	0.38	0.44	
	08	40	3.7	0.45	0.51	
	10 LA	31	4.5	0.90	1.04	
	10	42	5.4	0.59	0.68	
	12	44	7.1	0.71	0.82	
55	06	38	2.5	0.33	0.39	
	07 LA	25	2.3	0.71	0.82	
	07	41	3.3	0.38	0.44	
	08	41	4.1	0.47	0.54	
	10 LA	32	5.0	0.94	1.09	
	10	43	6.0	0.62	0.72	
	12	45	7.9	0.75	0.87	
60	06	38	2.6	0.35	0.40	
	07 LA	25	2.4	0.74	0.85	
	07	41	3.5	0.40	0.46	
	08	42	4.2	0.46	0.53	
	10 LA	32	5.4	1.02	1.17	
	10	44	6.4	0.64	0.74	
	12	45	8.4	0.80	0.92	

Maxi-Paw™ / Maxi-Paw SAM Performance							METRIC
Pressure bar	Nozzle	Radius m	Flow m³/h	Flow l/m	Precip mm/h	Precip mm/h	
2.0	6	-	-	-	-	-	
	07 LA	6.8	0.38	6.0	16	19	
	7	10.4	0.55	9.0	10	12	
	8	11.0	0.68	11.4	11	13	
	10 LA	8.1	0.83	13.8	25	29	
	10	11.9	1.01	16.8	14	16	
	12	12.3	1.32	22.2	18	20	
2.5	6	11.3	0.46	7.8	7	8	
	07 LA	7.1	0.44	7.2	17	20	
	7	11.4	0.62	10.2	10	11	
	8	11.7	0.76	12.6	11	13	
	10 LA	8.9	0.92	15.6	23	27	
	10	12.5	1.11	18.6	14	16	
	12	12.9	1.45	24.0	18	20	
3.0	6	11.5	0.51	8.4	8	9	
	07 LA	7.5	0.47	7.8	17	19	
	7	11.8	0.67	11.4	10	11	
	8	12.1	0.83	13.8	11	13	
	10 LA	9.4	1.01	16.8	23	27	
	10	12.8	1.21	20.4	15	17	
	12	13.3	1.59	26.4	18	21	
3.5	6	11.6	0.55	9.0	8	9	
	07 LA	7.6	0.50	8.4	17	20	
	7	12.2	0.72	12.0	10	11	
	8	12.4	0.89	15.0	12	13	
	10 LA	9.6	1.09	18.0	23	27	
	10	13.0	1.30	21.6	15	18	
	12	13.6	1.72	28.8	19	21	
4.0	6	11.6	0.58	9.6	9	10	
	07 LA	7.6	0.54	9.0	18	21	
	7	12.5	0.78	13.2	10	11	
	8	12.7	0.94	15.6	12	14	
	10 LA	9.8	1.19	19.8	25	29	
	10	13.3	1.42	23.4	16	19	
	12	13.7	1.86	31.2	20	23	

Precipitation rates based on half-circle operation

■ Square spacing based on 50% diameter of throw

▲ Triangular spacing based on 50% diameter of throw

Performance data collected in zero wind conditions

Performance data derived from tests that conform with ASAE Standards; ASAE S398.1.

See page 224 for complete ASAE Test Certification Statement.